

Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/US2006/001027

International filing date: 10 January 2006 (10.01.2006)

Document type: Certified copy of priority document

Document details: Country/Office: US
Number: 60/643,661
Filing date: 13 January 2005 (13.01.2005)

Date of receipt at the International Bureau: 20 March 2006 (20.03.2006)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse

1439849

THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

March 13, 2006

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE.

APPLICATION NUMBER: 60/643,661

FILING DATE: *January 13, 2005*

RELATED PCT APPLICATION NUMBER: *PCT/US06/01027*

THE COUNTRY CODE AND NUMBER OF YOUR PRIORITY APPLICATION, TO BE USED FOR FILING ABROAD UNDER THE PARIS CONVENTION, IS *US60/643,661*



Certified by

Under Secretary of Commerce
for Intellectual Property
and Director of the United States
Patent and Trademark Office

PROVISIONAL APPLICATION FOR PATENT COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53(c).

Express Mail Label No.

ET 793408978 US

113009 U.S.PTO
60/643661

INVENTOR(S)					
Given Name (first and middle [if any])		Family Name or Surname		Residence (City and either State or Foreign Country)	
Charles N.		Santry		Natick, Massachusetts	
Additional inventors are being named on the _____ separately numbered sheets attached hereto					
TITLE OF THE INVENTION (500 characters max)					
MULTI-VALVE FREEZE-PROOF DESIGN FOR SNOW MAKING					
Direct all correspondence to: CORRESPONDENCE ADDRESS					
<input checked="" type="checkbox"/> Customer Number: 45295					
OR					
<input type="checkbox"/> Firm or Individual Name					
Address					
Address					
City		State		Zip	
Country		Telephone		Fax	
ENCLOSED APPLICATION PARTS (check all that apply)					
<input checked="" type="checkbox"/> Specification Number of Pages 1					
<input type="checkbox"/> CD(s), Number _____					
<input checked="" type="checkbox"/> Drawing(s) Number of Sheets 3					
<input checked="" type="checkbox"/> Other (specify) Cover Sheet					
<input type="checkbox"/> Application Date Sheet. See 37 CFR 1.76					
METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT					
<input checked="" type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27.					
<input checked="" type="checkbox"/> A check or money order is enclosed to cover the filing fees.					
<input type="checkbox"/> The Director is hereby authorized to charge filing fees or credit any overpayment to Deposit Account Number: _____					
<input type="checkbox"/> Payment by credit card. Form PTO-2038 is attached.					
FILING FEE Amount (\$) \$100.00					
The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.					
<input checked="" type="checkbox"/> No.					
<input type="checkbox"/> Yes, the name of the U.S. Government agency and the Government contract number are: _____					

[Page 1 of 2]

Respectfully submitted,

SIGNATURE

Floyd B. Carothers

TYPED or PRINTED NAME Floyd B. Carothers

TELEPHONE (412) 471-3575

Date January 13, 2005

REGISTRATION NO. 24,252

(if appropriate)

Docket Number: 4418

USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

This collection of information is required by 37 CFR 1.51. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Mail Stop Provisional Application, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

Multi-Valve Freeze-Proof Design for Snowmaking

The following invention involves incorporating the internal components of a ball valve into a manifold attached to a snowgun in order to control water flow to the snowgun in a way that prevents the valve from freezing. Additionally, the design, by incorporating the components in a common manifold, reduces manufacturing costs and the overall size and weight of the snowgun.

One or multiple valves can be used in this configuration depending on the snowgun design. This concept can be used with internal or external mixing snowguns, ground/sled mounted or tower snowguns.


By burying the components of each valve into a manifold (part # 1) attached to the snowgun, all valve components are surrounded by moving water which is flowing through the snowgun while it is running. Water enters the manifold through a hose connection at A. All valve components are located in an open cavity within #1 through which all the water entering the snowgun must flow. The cavity is designed with enough room to allow this moving, relatively warm (above freezing) water to surround all the valve components and prevent these valve components from freezing whether the valves are in the open or closed positions. When a valve is turned on, water from the manifold travels up a separate chamber (#4) to feed additional nozzles at the snowgun head. When the valve is turned off, excess water left in this separate chamber drains out the drain port to prevent freezing of that separate chamber when not running.

These separate chambers which feed additional nozzles can be a series of pipes or separate channels within a multi lumen custom extrusion.


Valve seats for each of the valves are located in the manifold. Some are separate pieces threaded into place (part #2), others are machined into the base manifold. The ball is then located between the seats in the manifold. The stem which links to the ball extends out through the side of the manifold with a gland seal to prevent leakage. The valve can be manually activated by turning a valve handle (part #3) or automatically actuated by a mechanical actuator mounted on the manifold.

This manifold can be welded onto, or bolted onto, the snowgun.


Respectfully submitted by,



Charles N. Santry
President
Snow Economics, Inc.







BEST AVAILABLE COPY



VALVE SEATS

2





BEST AVAILABLE COPY